

5920836




FIG. 1
PRIOR ART




FIG. 2
PRIOR ART




FIG. 3
PRIOR ART

91

114




FIG. 4

```

-DRAGONDICTATE PROGRAM~144
  -INITIALIZE~204
  -TERMINATE AND STAY RESIDENT~206
  -GET USER INPUT BY MONITORING KEYSTROKE INTERRUPTS AND, IF
  MICROPHONE IS ON, UTTERANCE INTERRUPTS~208
  -IF RECEIVED KEYSTROKE IS:~210
    -"+", CALL VOICE CONSOLE SUBROUTINE
    -"-", CALL OOPS BUFFER SUBROUTINE
    -...
    -ANY OTHER KEY, PASS TO ACTIVE PROGRAM
  -IF RECEIVE UTTERANCE~212
    -CALL RECOGNIZER~214
    -IF BEST SCORING WORD IS:~216
      -CHOICE COMMAND SELECTING A WORD IN ALTERNATE CHOICE
      WINDOW~226
      -IF CHOICE COMMAND SELECTS OTHER THAN BEST SCORING
      WORD~228
        -SIMULATE TYPING NUMBER OF BACKSPACE CHARACTERS
        EQUAL TO NUMBER OF CHARACTERS IN FIRST CHOICE
        WORD~230
        -SIMULATE TYPING CHARACTERS OF SELECTED WORD~232
      -REMOVE CHOICE WINDOW~234
      -MAKE SELECTED WORD FIRST CHOICE~236
      -SET UTTERANCE'S CONFIRMED_FLAG~254
      -CALL ADAPTIVE TRAINING SUBROUTINE FOR CONFIRMED
      UTTERANCE AND FIRST CHOICE WORD~256
    -"CHOOSE-10", OR "SCRATCH THAT"~360
      -BACKSPACE NUMBER OF CHARACTERS IN BEST SCORING
      WORD~362
      -REMOVE CHOICE WINDOW~364
      -REMOVE UTTERANCE'S ENTRY IN OOPS BUFFER~366
    -"OOPS"~368
      -CALL OOPS_SUBROUTINE~370
    -...
  -NOT ONE OF ABOVE COMMANDS~218
    -REMOVE PREVIOUS CHOICE WINDOW IF ANY~223
    -SIMULATE TYPING OF UTTERANCE'S BEST SCORING WORD~220
    -PLACE CHOICE WINDOW ON SCREEN NEAR CURSOR~222
    -IF CONFIRMED_TRAINING_ONLY_FLAG IS FALSE OR IF THE
    CONFIRMED_FLAG OF THE OLDEST ENTRY IN THE OOPS BUFFER
    IS SET~392
      -CALL ADAPTIVE TRAINING SUBROUTINE FOR TOKEN OF
      THE OLDEST ENTRY IN THE OOPS BUFFER AGAINST THAT
      ENTRY'S FIRST CHOICE WORD, UNLESS ALREADY
      DONE~394

```

FIG. 5

-CALL UPDATE ONEGRAM, UPDATE DIGRAM,
 AND UPDATE CONTEXT LANG MODEL
 SUBROUTINES BASED ON OLDEST ENTRY'S
 FIRST CHOICE WORD~396
 -IF SAVING_TOKEN_FLAG IS SET, SAVE OLDEST
 ENTRY'S TOKEN LABELED WITH ITS FIRST CHOICE WORD
 IN A FILE, BUFFERING SAVES TO REDUCE DISK
 ACCESS~398
 -ADD NEW ENTRY TO OOPS BUFFER FOR LAST UTTERANCE,
 INCLUDING ITS TOKEN, NINE BEST SCORING WORDS, AND A
 ZEROED CONFIRM_FLAG~400

FIG. 5 CONT.

-VOICE CONSOLE SUBROUTINE~146
 -IF SYSTEM HAS ONE OR MORE USER FILES DEFINED~402
 -ENABLE FULL VOICE CONSOLE MENU
 -IF NOT~404
 -LIMITED VOICE CONSOLE MENU TO LOAD USER OR EXIT
 -VOICE CONSOLE LOOP~406
 -CLEAR OTHER PROMPTS, IF ANY, AND DISPLAY VOICE CONSOLE
 MENU~408
 -GET USER INPUT~410
 -IF INPUT IS:~412
 -"LOAD USER"~414
 -PROMPT FOR USER NAME~416
 -GET INPUT~420
 -IF USER ENTERS A NEW USER NAME~422
 -PROMPT IF WANT TO CREATE NEW USER~424
 -IF NOT, RETURN TO TOP OF VOICE CONSOLE LOOP~426
 -IF SO~428
 -PROMPT IF WANT TO RUN TUTORIAL~430
 -IF USER SELECTS YES~432
 -EXIT VOICE CONSOLE
 -LOAD AND RUN TUTORIAL
 -ELSE~434
 -EXIT VOICE CONSOLE
 -LOAD AND RUN SELECT_BASE_VOCAB
 PROGRAM
 -SELECT USER'S .VOC AND .USR FILES FOR USE BY
 RECOGNIZER~446
 -EXIT VOICE CONSOLE~448
 -...
 -"UTILITIES"~450
 -DISPLAY UTILITIES MENU~452

FIG. 6

```

-GET INPUT~452
-IF INPUT IS:
-...
  -"PARAMETERS",~454
    -DISPLAY PARAMETERS MENU~456
    -GET INPUT~456
    -IF INPUT IS
      -...
      -"CONFIRMED TRAINING ONLY", SET
      CONFIRMED_ TRAINING_ ONLY_ FLAG~468
      -"SAVE TOKEN", SET SAVE_TOKEN_FLAG~460
      -...
    -...
  -...
-...
-...

```

FIG. 7

- OOPS BUFFER~160
 - ENTRY1
 - ENTRY2
 - ENTRY3~238
 - ENTRY4
 - ENTRY5~238
 - ENTRY6~238
 - ENTRY7
 - ENTRY8
 - ENTRY9
 - ENTRY10
 - ENTRY11
 - ENTRY12
 - READ/WRITE POINTER~240

FIG. 8

- OOPS BUFFER ENTRY~238
 - TOKEN~244
 - WORD_1~246A
 - WORD_2
 - WORD_3~246
 - WORD_4
 - WORD_5~246
 - WORD_6~246
 - WORD_7
 - WORD_8
 - WORD_9
 - VOCABULARY~248
 - STATE~250
 - CONFIRMED_FLAG~252

FIG. 9

- USERNAME.VOC FILE~162
 - LIST OF WORDS~260
 - FOR EACH
 - WORD~263
 - PHONEME SPELLING LIST~262
 - PHONETIC SPELLINGS~263
 - PREFIXING WORD START~264
 - LIST OF STATES~266
 - FOR EACH
 - STATE~267
 - LIST OF WORDS OR INCLUDED STATES~268
 - FOR EACH
 - WORD OR STATE~269

FIG. 10

- TRANSITION TO ANOTHER STATE~270
- EXTRA DATA (SUCH AS KEYSTROKE SEQUENCE)~272
- DEFAULT TRANSITION~274
- DEFAULT EXTRA DATA~276

FIG. 10 CONT.

- USERNAME.USR FILE~164
 - PREFILTERING MODELS~280
 - PIC TABLE~282
 - FOR EACH PHONEME TRIPLE
 - ITS ASSOCIATED SEQUENCE OF PELS~284
 - DURATION MODEL~286
 - PEL MODEL LIST~288
 - FOR EACH PEL
 - PEL ID~291
 - 1 AMPLITUDE PARAMETER~290
 - 7 SPECTRAL PARAMETERS~292
 - 12 CEPSTRAL PARAMETERS~294
 - HELPER MODEL LIST~296
 - FOR EACH WORD FOR WHICH USER UTTERANCES SCORE POORLY AGAINST PHONETIC MODEL
 - WORD~298
 - PHONETIC MODEL OF WORD, IF ANY~300
 - SEQUENCE OF PELS~302
 - PREFILTERING WORD START~303

FIG. 11

- ADAPTIVE TRAINING SUBROUTINE~152
 - ADJUST WEIGHT TO BE GIVEN TOKEN IN TRAINING ACCORDING TO SUCH FACTORS AS STATE OF CONFIRMED_FLAG~304
 - CALL WORD_TRAINING FOR WORD, TOKEN, AND WEIGHT~306

FIG. 12

- TRAINING SUBROUTINE (TOKEN LIST, WORD MODEL)~326
 - FOR EACH TOKEN IN TOKEN LIST~330
 - TIME ALIGN AND SCORE PARAMETER VECTORS OF TOKEN AGAINST PELS OF WORD MODEL~332
 - UPDATE PELS OF WORD MODEL WITH VECTORS TIME ALIGNED AGAINST THEM~334

FIG. 13

-CALL ADAPTIVE_TRAINING SUBROUTINE FOR
 TOKEN, AND ANY SIMILAR TOKEN[X]s FROM
 PREVIOUS LOOP, AND BEST SCORING
 ALLOWED RESPONSE WORD, IF THAT WORD IS
 THE EXPECTED WORD~550
 -LABEL TOKEN WITH BEST SCORING ALLOWED RESPONSE WORD,
 IF THAT WORD IS THE EXPECTED WORD~552
 -RETURN~553
 -IF USER_RESPONSE IS ZERO~554
 -SAVE TOKEN AS TOKEN[UTTERANCE_NUMBER]~556
 -IF UTTERANCE_NUMBER = 1~558
 -PROMPT USER TO REPEAT WHAT JUST SAID
 -OTHERWISE~560
 -PROMPT USER TO SAY EXPECTED WORD~562
 -IF UTTERANCE_NUMBER >2~564
 -COMPARE TOKEN[X]s WITH EACH OTHER~566
 -IF THREE SCORE WITHIN A GIVEN DISTANCE OF EACH
 OTHER~568
 -LABEL THE THREE CLOSELY SCORING TOKEN[X]s
 WITH EXPECTED WORD~570
 -SET USER_RESPONSE TO EXPECTED WORD~572
 -EXIT UTTERANCE_LOOP~574
 -ELSE IF UTTERANCE_NUMBER = 5,~576
 -LABEL THREE TOKEN[X]s WHICH COMPARE MOST
 CLOSELY AS EXPECTED WORD~578
 -SET USER_RESPONSE TO EXPECTED WORD~580
 -EXIT UTTERANCE_LOOP~582
 -IF USER_RESPONSE IS NOT ZERO~584
 -CALL ADAPTIVE TRAINING SUBROUTINE FOR UTTERANCE'S THREE BEST
 SCORING TOKEN[X]s AND EXPECTED WORD~
 -SAVE THREE CLOSEST TOKEN[X]s, LABELED BY THEIR ASSOCIATED
 EXPECTED WORD~585

FIG. 21 CONT.

202

C:\VT > vt 200

C:\VT > voicetyp.exe
 DOS/16M Protected Mode RunTime Version 4.20
 Copyright (C) Rational Systems, Inc. 1987 - 1992
 Dragon Systems Speech Driver Version 4.04.28 ALPHA INHOUSE ACPA 32PAR
 For use with the IBM VoiceType (TM) Speech Recognition System
 (C) Copyright Dragon Systems, Inc. 1986-1992

VoiceConsole

Plus Turn microphone on

G GO TO SLEEP

E EDIT words

S SAVE vocabulary

N LOAD USER

R REVERT TO SAVED

T TRAIN

L TUTORIAL

U UTILITIES

C CONTINUE

MIC=OFF [Default Application]

DragonD 1991,1992

(C) Cop on contained herein *****

AEI # :BCR-0113.

INHOUSE

Press P

C:\VT >

C:\VT >

401

Figure 22

C:\VT > vt

C:\VT > voicetyp.exe
DOS/16M Protected Mode RunTime Version 4.20
Copyright (C) Rational Systems, Inc. 1987 - 1992
Dragon Systems Speech Driver Version 4.04.28 ALPHA INHOUSE ACPA 32PAR
For use with the IBM VoiceType (TM) Speech Recognition System
(C) Copyright Dragon Systems, Inc. 1986-1992

DragonD VoiceConsole
(C) Cop nc. 1990,1991,1992
**** information contained herein *****
**** proprietary and should be *****
**** Agreement AEI #:BCR-0113. *****

INHOUSE

Press P

401A

Turn microphone on

GO TO SLEEP

EDIT words

SAVE vocabulary

LOAD USER

REVERT TO SAVED

TUTORIAL

UTILITIES

CONTINUE

MIC-OFF

C:\VT >
C:\VT >

Figure 23

GetValidEvent(mask=1)

Globals:

472 ✓
TIMEOUT 40 (moff) (noclr) --> CALL global-mic-off
ANYKEY (moff) (noclr) --> CALL global-mic-off
ANYKEY (norm) (nxpg) (moff) (noclr) --> CALL global-unknown-key
KEY 'Enter' (norm) (nxpg) (moff) (noclr) --> CALL global-key-not-now
KEY 'KeyPadEnter' (norm) (nxpg) (moff) (noclr) --> CALL global-key-not-now
ANYSPELLKEY (norm) (nxpg) (moff) (noclr) --> CALL global-key-not-now
KEY '+' (norm) (nxpg) (moff) (noclr) --> CALL global-wrong-plus-key
KEY '-' (norm) (nxpg) (moff) (noclr) --> CALL global-wrong-minus-key
TIMEOUT 40 (norm) (nxpg) (noclr) --> CALL global-timeout
KEY 'F1' (norm) (nxpg) (moff) (noclr) --> CALL global-get-help
UTT "[get help]" (norm) (nxpg) (noclr) --> CALL global-get-help
UTT_TOO_LOUD (norm) (nxpg) (moff) (noclr) --> CALL global-too-loud
UTT_TOO_SOFT (norm) (nxpg) (moff) (noclr) --> CALL global-too-soft
REJECTED_UTT (norm) (nxpg) (moff) (noclr) --> CALL global-rejected-utt
UTT_STRANGE (norm) (nxpg) (moff) (noclr) --> CALL global-rejected-utt
TALK_TOO_FAST (norm) (nxpg) (moff) (noclr) --> CALL global-talk-too-fast
UTT_TOO_LONG (norm) (nxpg) (moff) (noclr) --> CALL global-utt-too-long
KEY 'Esc' (norm) (nxpg) (moff) (noclr) --> CALL global-escape
KEY 'Minus' (norm) (nxpg) (moff) (svmsg) --> CALL global-mainmenu
UTT "[Tutor menu]" (norm) (nxpg) (svmsg) --> CALL global-mainmenu
KEY 'Plus' (norm) (nxpg) (moff) (svmsg) --> CALL global-voice-console
UTT "[voice console]" (norm) (nxpg) (svmsg) --> CALL global-voice-console

Defaults:

474 ✓
LASTWORD "[new paragraph]" (norm) (noclr) --> CALL default-lastword
NEXTWORD ", "comma" (norm) (noclr) --> CALL default-nextword
LASTWORD "[new paragraph]" (nxpg) (noclr) --> CALL default-nextpage
CURWORD "down" (nxpg) (noclr) --> CALL default-nextpage
NEXTWORD ", "comma" (nxpg) (noclr) --> CALL default-nextpage
KEY 'F2' (norm) (noclr) --> CALL default-no-function-keys
KEY 'F3' (norm) (noclr) --> CALL default-no-function-keys
KEY 'F4' (norm) (noclr) --> CALL default-no-function-keys
KEY 'FS' (norm) (noclr) --> CALL default-no-function-keys
KEY 'F6' (norm) (noclr) --> CALL default-no-function-keys
KEY 'F7' (norm) (noclr) --> CALL default-no-function-keys
KEY 'F8' (norm) (noclr) --> CALL default-no-function-keys
KEY 'F9' (norm) (noclr) --> CALL default-no-function-keys
KEY 'F10' (norm) (noclr) --> CALL default-no-function-keys
UTT "[oops!]" (norm) --> CALL d3gd-oops

476 ✓ Cases:

UTT "down" (norm) --> *e
UTT "[choose 1]" (norm) --> GOTO d2gd-said-okay
UTT "[okay]" (norm) --> GOTO d2gd-said-okay
KEY 'Backspace' (norm) --> CALL d2gd-ignore-backspace
LASTSPELLKEY '[' (norm) --> CALL d2gd-one-right
ANYSPELLKEY (norm) --> CALL d2gd-one-wrong

477 ✓ Ceiling:

End of Stack.

FIG. 28

```

*****
** MODULE NAME: final7.pln
** Copyright (c) Dragon Systems, Inc. 1992
** OWNER:      Joel Gould
** CREATED:    September 4, 1992
** FUNCTIONS
** DESCRIPTION
502 ** Chapter 7
** This topic teaches the user to correct dictation errors by
** selecting words from the choice list.
*****
** MODIFICATIONS
** ...
**
*****
504 CHAPTER Correcting Dictation with the Choice List

DEFAULT NOCLEAR LASTWORD      CALL default-lastword
DEFAULT NOCLEAR NEXTWORD      CALL default-nextword
DEFAULT NEXTPAGE NOCLEAR LASTWORD CALL default-nextpage
DEFAULT NEXTPAGE NOCLEAR CURWORD CALL default-nextpage
DEFAULT NEXTPAGE NOCLEAR NEXTWORD CALL default-nextpage
DEFAULT NOCLEAR 'F2'          CALL default-no-function-keys
DEFAULT NOCLEAR 'F3'          CALL default-no-function-keys
506 DEFAULT NOCLEAR 'F4'          CALL default-no-function-keys
DEFAULT NOCLEAR 'F5'          CALL default-no-function-keys
DEFAULT NOCLEAR 'F6'          CALL default-no-function-keys
DEFAULT NOCLEAR 'F7'          CALL default-no-function-keys
DEFAULT NOCLEAR 'F8'          CALL default-no-function-keys
DEFAULT NOCLEAR 'F9'          CALL default-no-function-keys
DEFAULT NOCLEAR 'F10'         CALL default-no-function-keys
DEFAULT NOCLEAR ANYSPELLKEY   CALL default-no-spelling-keys

* IF INORDER GOTO chap7-start

508 EDITOR RESET

* LESSON chap7-start

510 CONSOLE MIC ON
512 CONSOLE SLEEP OFF
514 PROMPT HIDE
EDITOR SHOW
*-----
516 (HIGH)TOPIC: CORRECTING DICTATION WITH THE CHOICE LIST(NORM)
. This topic describes how to use the choice list to correct dictation
. errors. You are going to learn how to:
. \p Accept (NAMENORM)'s default choice
. \p Choose another word from the choice list

```

FIG. 30

Please say (SAY)"[okay]" to continue.(CR)
Please say (UTT)"[Tutor menu]" to display the menu.

518 ~EXPECTING "[okay]"

IF INORDER CALL chap7-bonus-text

590 { PROMPT RESET
PROMPT SHOW
PROMPT HIGHLIGHT OFF

*
*

* PROMPT /when/suddenly/a/white/rabbit/with/pink/eyes/

* PROMPT /ran/close/by/her/. \"period\"/

PROMPT /[new paragraph]/

PROMPT /there/was/nothing/so/very/remarkable/in/that/; \"semicolon\"/

PROMPT /nor/did/Alice/think/it/so/very/much/out/of/the/way/to/

PROMPT /hear/the/rabbit/say/to/itself/, \"comma\"/\" \"open quote\"/

PROMPT /oh/dear/! \"exclamation point\"/oh/dear/! \"exclamation point\"/

PROMPT /I/shall/be/too/late/! \"exclamation point\"/\" \"close quote\"/

PROMPT /(\"open paren\"/when/she/thought/it/over/afterwards/, \"comma\"/

PROMPT /it/occurred/to/her/that/she/ought/to/have/wondered/at/this/, \"co

PROMPT /but/at/the/time/it/all/seemed/quite/natural/) \"close paren\"/;

\"semicolon\"/

596 ~PROMPT HIGHLIGHT ON

598 { Since you are starting a new topic, please start a new paragraph
in your document. Say (SAY)"[new paragraph]".

602 ~EXPECTING "[new paragraph]"

604 ~CHOICELIST 1="[new paragraph]"

606 { Please begin dictating this lesson by saying the first word in the
Text Prompter, (SAY)"there".

610 ~EXPECTING "there"

612 ~CHOICELIST 1="there"

616 { This is a choice list, which has appeared every time you've dictated a w
If the word you said is correctly identified, it is listed first on the
choice list. However, you still have to tell (NAMENORM) that this
recognition is correct.

There are three ways to do this.

620 ~NEWPAGE

622 { The first is to say the next word. This

FIG.30 CONT.-1

622 { is the method you used in the previous topic.
 { The second way is to say (UTT)"[okay]". You used this method in earlier topics.
 { The third way is to say (UTT)"[choose 1]", since you want to choose the first word on the choice list.

626 ~NEWPAGE

630 { Until now, the word the Text Prompter asked you to dictate has always appeared as the first word on the choice list. But that doesn't always happen when you dictate in (NAMENORM).
 { Sometimes the word you dictate will be an alternate choice on the list.
 { Sometimes it won't be on the list at all.
 { Please continue dictating from the Text Prompter, starting with (SAY)"was".

636 ~EXPECTING "was"

638 ~call dictatel-no-error * next: "nothing"

640 ~call dictatel-no-error * next: "so"

652 { Sometimes (NAMENORM) identifies the word said as a possibility, but not as the most likely choice. When this happens, the word will appear on the choice list, but not as the first choice.
 { Please dictate the next word.

656 ~call dictatel-no-error * next: "very"

660 ~CHOICELIST 1="vary" 3="very"

666 ~POINTAT CHOICELIST 3

668 { Although you said (UTT)"very", (NAMENORM) thought that the most likely thing that you said was (UTT)"vary".
 { (NAMENORM) learns from its mistakes and adapts to your style of speech. Therefore, you must correct any recognition errors immediately.

NEWPAGE

672 { If you fail to correct (NAMENORM)'s mistake in this case, every time you say (UTT)"very", it will type (UTT)"vary". If this mistake goes by undetected, other words are also affected.
 { The next time you say (UTT)"merry", (NAMENORM) may think you mean (UTT)"marry".

NEWPAGE

FIG.30 CONT-2

676 { If, as in this case, the word you spoke is not in the first position on the choice list, you must tell {NAMENORM} which word you actually spoke. You do this with the {UTT}"[choose n]" command, where {UTT}"n" is the number of the word on the choice list.

NEWPAGE

680 { In this case, you want {NAMENORM} to select the third word.
Please say {SAY}"[choose 3]" now.

684 ~ CASE {NEXTWORD} CALL must-say-choose-n

686 ~ EXPECTING "[choose 3]"

*-----

688 ~ CHOOSE 3

692 { Saying {UTT}"[choose 3]" made {NAMENORM} erase the word {UTT}"vary" from the text and type the word {UTT}"very" instead.

Because you chose the word you spoke, {NAMENORM} no longer needs to show a list of possible interpretations of the utterance and it has removed the choice list from the screen.

As soon as you say the next word, the choice list will re-appear with a new set of possibilities.

NEWPAGE

For the rest of this tutorial, the {NAMENORM} Tutorial will allow random recognition errors to occur while you practice your dictation. Correct them as soon as they happen, to prevent corruption of your vocabulary.

696 { If {NAMENORM} correctly identifies the word you say, continue on to the next word. If it incorrectly identifies the word you say, correct it by saying {UTT}"[choose n]", where {UTT}"n" is the number of the desired word on the choice list. If you don't correct your errors, the Tutorial will remind you.

To start dictating again, please say the next word on your Text Prompter, {SAY}"remarkable".

700 ~ EXPECTING "remarkable"

*-----

702 ~ call dictatel-no-error

* next: "in"

708 ~ call dictatel-no-error

* next: "that"

714 ~ CHOICELIST 1={CURWORD}

720 ~ Please say {SAY}"; \"semicolon\"".

FIG.30 CONT-3

724 { CASE "[choose 1]" CALL dlgd-said-okay
CASE "[okay]" CALL dlgd-said-okay
726 ~ EXPECTING "; \"semicolon\""

728 ~ call dictatel-no-error * next: "nor"

*-----
*must-correct-errors

734 { Notice that the word "nor" did not appear first on
your choice list. Please choose the correct word now,
and then continue dictating.

738 ~ CALL dictatel-on-list * next: "did"

762 { CHOICELIST 1=(CURWORD)
CASE "[choose 1]" CALL dlgd-said-okay
CASE "[okay]" CALL dlgd-said-okay
EXPECTING "Alice"

*-----
* expecting:

766 ~ CALL dictatel-no-error	* think
768 ~ CALL dictatel-no-error	* it
770 ~ CALL dictatel-on-list	* so
CALL dictatel-no-error	* very
CALL dictatel-no-error	* much
CALL dictatel-on-list	* out
CALL dictatel-on-list	* of
CALL dictatel-no-error	* the
CALL dictatel-no-error	* way
CALL dictatel-no-error	* to
CALL dictatel-no-error	* hear
CALL dictatel-no-error	* the
CALL dictatel-on-list	* rabbit
CALL dictatel-no-error	* say
CALL dictatel-no-error	* to
CALL dictatel-on-list	* itself
CALL dictatel-no-error	* , \"comma\"
CALL twoword1-open-quote	* \" \"open quote\"
	* oh
CALL dictatel-no-error	* dear

{NAMENORM} has two words for the {UTT}'!' character:
{UTT}'! \"exclamation point\" and
{UTT}'! \"exclamation mark\".

While you use the {NAMENORM} Tutorial, however,
only {UTT}'! \"exclamation point\" is active.

FIG.30 CONT-4


```

*
* ---> DICTATE1-NO-ERROR
*
* Put current word first on choice list, then get the next word
*
640~LESSON dictatel-no-error
640A~CHOICELIST 1={CURWORD}
640B~LESSON dictatel-no-error-after
640C~HIGHLIGHT NEXTWORD * LASTWORD <- CURWORD
640D~CASE "[okay]" GOTO dlgd-said-okay
640E~CASE "[choose 1]" GOTO dlgd-said-okay
640F~EXPECTING {CURWORD}
640G~RETURN
*-----
* We end up here if the user has said OKAY or something else which
* accepts the last word and clears the choice list. Here we expect
* him, to say the next word.
*
646~LESSON dlgd-said-okay
646A~CHOOSE {LASTWORD}
646B~EXPECTING {CURWORD}
646C~RETURN
*-----
*****
*
* ---> DICTATE1-ON-LIST
*
* Pick a random slot for the word to appear which is not the first
* slot on the choice list. Make sure the user says "choose-N",
* then get the next word
*
740~LESSON dictatel-on-list
740A~CHOICELIST ?={CURWORD}
740B~HIGHLIGHT NEXTWORD * LASTWORD <- CURWORD
740C~CASE {CURWORD} CALL dlon-say-choose-n
740D~CASE "[okay]" CALL dlon-say-choose-n
740E~CASE "[choose 1]" CALL dlon-say-choose-n
740F~EXPECTING "[choose {?)]"
740G~CHOOSE (?)
740H~EXPECTING {CURWORD}
740I~RETURN
*-----
746~LESSON dlon-say-choose-n
746A~AFTERSEEN 1 dlon-short1-say-choose-n

746B { The performance of {NAMESHORT} improves with every error it makes,
      but only if you correct the mis-recognitions. If you do not correct
      every error, {NAMESHORT}'s performance will get worse.

      {NAMESHORT} has incorrectly identified the word you just spoke.

```

FIG.31 CONT.-1

The correct word {UTT}{LASTWORD} is on the choice list, however,
and you can correct {NAMESHORT}'s mis-recognition. Please {WHAT2DO}.

746D ~ REMOVEUTT

746E ~ RETURN REPEAT

*-----

748 ~ LESSON dlon-short1-say-choose-n

748A ~ RANDOMIZE 25 dlon-short2-say-choose-n

748B ~ RANDOMIZE 33 dlon-short3-say-choose-n

748C ~ RANDOMIZE 50 dlon-short4-say-choose-n

748D { Please correct {NAMESHORT}'s mis-recognition before continuing.
Please {WHAT2DO}.

748E ~ REMOVEUTT

748F ~ RETURN REPEAT

*-----

750 ~ LESSON dlon-short2-say-choose-n

Please {WHAT2DO} to correct that last mis-recognition.

REMOVEUTT

RETURN REPEAT

*-----

752 ~ LESSON dlon-short3-say-choose-n

It is very important to correct all mis-recognitions to
prevent your vocabulary files from being corrupted.

Please say {SAY}{EXPECTED}.

REMOVEUTT

RETURN REPEAT

*-----

754 ~ LESSON dlon-short4-say-choose-n

Correct the last error before continuing to dictate.

REMOVEUTT

RETURN REPEAT

*-----

FIG.31 CONT-2

* ---> DICTATE3-RANDOM

*

* Currently forces an on-list error if we just had a misrecognition.

* Also introduces errors 5% of the time (just to be sure we get one)

*

* When an error is indicated, we choose on-list 60% of the time and

* off-list 40% of the time.

*

779~LESSON dictate3-random

779A~IF SHORTWORD GOTO dictate3-no-error

779B~RANDOMIZE 50 dictate3-no-error

779C~IF MISRECOG GOTO d3-error

779D~RANDOMIZE 5 d3-error

779E~GOTO dictate3-no-error

*-----

779F~LESSON d3-error

779G~RANDOMIZE 60 dictate3-on-list

779H~GOTO dictate3-off-list

*-----

FIG.31 CONT-3

TOPIC: CORRECTING DICTATION WITH THE CHOICE LIST

This topic describes how to use the choice list to correct dictation errors. You are going to learn how to:

- Accept DragonDictate's default choice
- Choose another word from the choice list

Please say "[okay]" to continue.

Please say "[Tutor menu]" to display the menu.

F1="get help" Minus=save/quit Plus=mic on/off

Pln 1 Topic 8 Ln 6

Figure 32


```
-CallWndProc(Code, wParam, lParam)-1029
  -if message is WM_INITMENU, indicating a menu is about to become
  active-1664
    -clear MenuStack-1666
    -place a MenuEntry with the MenuHandle indicated by WM_INITMENU
    in the MenuStack-1668
  -if message is WM_INITMENUPOPUP, indicating a popup menu is about to
  become active-1670
    -if a MenuEntry with the pop-up menu's menu handle in the
    MenuHandle field is not currently at the end of the MenuStack,
    add such an entry and place in the preceding entry in the
    MenuStack the MenuItemID corresponding to the item in the
    parent menu from which the popup menu came-1672
  -if message is WM_MENUSELECT, indicating a user has selected a menu
  item-1674
    -scan the MenuStack for an entry with MenuHandle matching
    that in the WM_MENUSELECT message-1676
    -if find a match-1678
      -if find the match other than at the end of the
      MenuStack, delete the MenuEntries after the matching
      MenuEntry from the stack-1680
      -record the menu item ID returned by WM_MENUSELECT in
      the MenuItemID field of the MenuEntry with the
      matching MenuHandle-1682
    -else use calls to MSW GetSubMenu to do a tree search,
    starting with menu handle returned by GetMenu, until find
    the menu with selected item, and then reestablish the
    MenuStack with the path in the menu tree which leads to
    menu of the selected item.-1684
  -if message is WM_NCDESTROY, indicating a window is being
  closed-1686
    -if WM_NCDESTROY is being sent to a window having a handle in
    the HWndToAppTable, delete that handle's entry in table-1688
  -if message is WM_ACTIVATE, indicating a window is being
  activated-1690
    -call ApplicationTracking with the window's HWnd-1692
    -pop-up any key alteration windows, if any, appropriate for the
    new active window-1693
  -if message is WM_CREATE, indicating a window is being created-1694
    -if the new window's handle is already in HWndToAppTable,
    delete the handle's entry in table-1696
  -if message is WM_SHOWWINDOW, indicating a window that was
  previously covered is being uncovered-1698
    -if a call to MSW GetWindow with GW_OWNER for the window
    indicates it is a application window or a dialog window, call
    ApplicationTracking with the window's HWnd-1700
  -return-1702
```

FIG. 49

-KeyboardProc(code, wParam, lParam)^1032

-...

-if ChoiceListOperative is true and the last message group header before the read pointer in the JournalPlaybackProc's message queue indicates the current message group was created for a word recognized from the "Choice List" state^1033

-use MSW PostMessage to send keystroke information represented by wParam and lParam to ChoiceList^1035

-return with indication the keystroke message which caused KeyboardProc to be called should be discarded^1037

-...

FIG. 50

-MenuStack^1036

-list of MenuEntry structs^1854, each containing

-MenuHandle^1856

-MenuItemID^1858

FIG. 51

-HwndToAppTable^1040

-a list of entry structs each containing^1654

-Hwnd^1656

-AppState^1658

-AppMode^1660

-ShiftKeyOn^1704

-ControlKeyOn^1706

-AltKeyOn^1708

FIG. 52

-store the utterance just recognized, and the LanguageContext
and StateList for the utterance, and its up to nine best
scoring words and their associated states in a
WordHistoryBuffer~1210
-call PerformWordsOutput for the best scoring word, its
associated state, and pointer into utterance's entry in
WordHistoryBuffer, if any~1212
-return~1214

-...

FIG. 54 CONT.

00002013-052697




Figure 61

```

-PerformWordsOutput(Word, State, WordHistoryBufferPointer)~1112
  -if ChoiceListOperative is true and the choice list is not the
    active window~1390
    -if State is not "Choice List" use MSW PostMessage to send
      RemoveChoiceList message to ChoiceList routine~1392
  -if Word has any ExtraData in its State~1394
    -if first byte in the ExtraData field indicates following bytes
      are DragonDictate script~1396
      -call MacroInterpreter to interpret the script~1398
      -return~1400
    -else if the first byte in the ExtraData field indicates the
      following bytes are to be fed to the JournalPlaybackProc~1402
      -copy the following ExtraData bytes to TextOutput~1404
  -else if Word has no ExtraData in its State~1406
    -copy the word's spelling (prior to " []", if any) to
      TextOutput~1408
  -if ShiftKeyOn is true for the currently active window~1410
    -capitalize first letter of TextOutput~1412
    -set ShiftKeyOn to false for the currently active window~1414
  -if ControlKeyOn is true for the currently active window~1416
    -replace first character of TextOutput with its control key
      equivalent~1418
    -set ControlKeyOn to false for the currently active window~1420
  -if AltKeyOn is true for the currently active window~1422
    -replace first character of TextOutput with its alt key
      equivalent~1424
    -set AltKeyOn to false for the currently active window~1426
  -copy a message group header, indicating whether or not the
    characters in TextOutput are associated with a word from the "Choice
    List" state, into the JournalPlaybackProc's message queue~1427
  -copy each character in TextOutput into the JournalPlaybackProc's
    message queue following the message group header~1428
  -call MSW SetWindowsHookEx with WH_JOURNALPLAYBACKPROC to install
    the hook for the JournalPlaybackProc~1430
  -if CurrentMode is DictateMode, and if the state of the best scoring
    word is other than "Choice List", use MSW PostMessage to send
    DisplayChoiceList message to ChoiceList routine with
    WordHistoryBufferPointer, which points to Word's associated the
    utterance just recognized in WordHistoryBuffer~1432

```

FIG. 64


```

-MacroInterpreter(MacroScript)^1382
  -create a MacroInstance for running of current MacroScript^1434
  -...
  -until reach end of the MacroScript^1386
    -find the next macro statement in the MacroScript^1438
    -if statement is^1440
      -"MenuPick[string]": call MenuPick subroutine for the
        string^1442
      -"ControlPick[string]": call ControlPick subroutine for
        the string^1444
      -"SpellMode": and if ChoiceListOperative is true^1446
        -make choice list the active window^1448
        -set CurrentMode to CommandMode^1450
      -"CommandMode":^1452
        -set CurrentMode to CommandMode^1454
        -set the AppMode associated with the currently active
        window in HWndToAppTable to CommandMode^1456
      -"DictateMode":^1458
        -set CurrentMode to DictateMode^1460
        -set the AppMode associated with the currently active
        window in HWndToAppTable to CommandMode^1462
      -"MicrophoneOff":^1464
        -set RecognizerOn to false^1466
        -set MicOffConfirmed to false^1468
      -"MicrophoneOn":^1470
        -set RecognizerOn to true^1472
        -set MicOffConfirmed to false^1473
      -"ShiftKey": set the ShiftKeyOn value in the currently
        active window's entry in the HWndToAppTable to true^1476
      -"ControlKey": set the ShiftKeyOn value in the currently
        active window's entry in the HWndToAppTable to true^1478
      -"AltKey": set the ShiftKeyOn value in the currently
        active window's entry in the HWndToAppTable to true^1480
    -...
  -delete current MacroInstance^1482
  -return^1484

```

FIG. 67

```

-JournalPlaybackProc(code, wParam, lParam)~1403
  -if code equals HC_GETNEXT~1487
    -copy the unread message element pointed to by, or following,
    the JournalPlaybackProc's read pointer to the location in
    memory pointed to by lParam~1488
  -else if code equals HC_SKIP~1489
    -increment the read pointer to the next unread message element,
    if there is one~1490
    -if the read pointer points past the last unread message
    element in the message queue~1492
      -call MSW UnhookWindowsHookEx for the JournalPlaybackProc
      to de-active its hook~1494
      -clear the message queue and zero the read and write
      pointers~1496
  -return~1498

```

FIG. 68

00000000 "00000000"

```

-WordTraining(Word, TokenList)~1311
  -if Word has one or more models~1502
    -if Word has more than one word model~1504
      -score each token in the TokenList against each of Word's
        word models~1506
      -associate each token with the word model against which it
        scores best~1508
    -else, associate each token with Word's single model~1510
  -for each of Word's pronunciations with which tokens have been
    associated ~1512
    -set GoodSpelledModelTokens and GoodHelperModelTokens to
      0~1516
    -if the pronunciation has a spelled model, call Training
      to adapt that spelled model with all the tokens associated
      with the pronunciation's phonetic or helper model, adding
      the number of such tokens that were successfully used to
      adapt the spelled model to GoodSpelledModelTokens~1518
    -if the pronunciation has a helper model, call Training to
      adapt that helper model with all the tokens associated
      with the pronunciation's phonetic or helper model, adding
      the number of such tokens that were successfully used to
      adapt the spelled component as GoodHelperModelTokens~1520
    -if GoodHelperModelTokens and GoodSpelledModelTokens are
      both 0~1522
      -if pronunciation has a helper model, delete it~1524
      -call TrainNewModel to build a new helper model for
        the pronunciation using all of the tokens associated
        with the pronunciation~1526
    -else, if there is a helper model and GoodHelper-
      ModelTokens is 0~1528
      -delete the helper model~1530
  -else if Word had no models~1532
    -call TrainNewModel to build a helper model for Word using all
      of the token in the TokenList~1534
  -return~1536

```

FIG. 69


```

        -"[Choose 5]" /keys {Alt+5}{Enter}
        -"[Choose 6]" /keys {Alt+6}{Enter}
        -"[Choose 7]" /keys {Alt+7}{Enter}
        -"[Choose 8]" /keys {Alt+8}{Enter}
        -"[Choose 9]" /keys {Alt+9}{Enter}
        -"[Choose 10]" /keys {Alt+0}{Enter}
        -...
-vocabulary Voicebar
    -group Voicebar
        -...
        -group "Train Word"~1285
            -"[Stop Training]" /keys {Alt+s}~1289
        -...

```

FIG. 71

— • • •

```

-FindOrMakeMatchingWord(String)~1336
  -scan .VOC file for word with a spelling matching String~1338
  -if find one, return with matching word's ID~1340
  -else~1342
    -create a new word ID in .VOC file, set its spelling equal to
      String, and give it an empty phonetic spelling list~1344
    -if String contains a portion of text inside a top level "[ ]",
      set String equal to that portion of text~1346
    -strip all punctuation characters besides apostrophes~1348
    -clear IDQueue~1350
    -for each successive word in String~1352
      -scan .VOC file for word with spelling matching the
        successive word~1354
      -if find one, place ID of word in IDQueue~1356
      -else~1358
        -return with the new word's ID~1360
    -place one empty phonetic spelling in the new word's phonetic
      spelling list~1362
    -for each ID in IDQueue~1364
      -if the ID's word has no phonetic spelling~1366
        -empty the word's phonetic spelling list~1368
        -return with the new word's ID~1370
      -for each phonetic spelling of the ID's word~1372
        -for each prior spelling in the new word's phonetic
          spelling list~1374
          -if the total number of spelling's in the
            phonetic spelling list created in conjunction
            with the current ID is less than
            SpellingNumberLimit, create a spelling which
            concatenates the ID's current phonetic spelling
            to the end of the prior phonetic spelling,
            altering phonemes near the boundary of its
            concatenated spelling if required by
            coarticulation rules~1376
        -remove the prior phonetic spellings~1378
    -return with new word's ID~1380

```

FIG. 72

```

-FindWordDialog~1550
  -...
  -message loop~1552
    -call MSW GetMessage~1554
    -if message is~1556
      -...
      -"Delete"~1558
        -if a word has been selected for deletion in
          conjunction with a given path listed in the
          Vocabulary/Group ComboBox, delete the selected word
          from the state indicated in the Vocabulary/Group
          ComboBox~1560
        -...
      -...
    -...

```

FIG. 73

```

-ApplicationTracking(HWnd)~1594
  -if HWnd is Null~1596
    -call MSW GetActiveWindow to get the handle of the currently
      active window~1598
    -set HWnd equal to active window handle~1600
  -if HWnd has an entry in HWndToAppTable, return with that entry as
    the SelectedEntry~1602
  -else~1604
    -add a new entry to HWndToAppTable with HWnd, CommandMode as
      its AppMode, an empty AppState, and ShiftKeyOn, ControlKeyOn,
      and AltKeyOn all set to false~1606
    -make the new entry the SelectedEntry~1608
    -call MSW GetWindowWord to get the hinstance of the program
      module running the HWnd's window~1610
    -call MSW GetModuleFileName for that hinstance to get the file
      name of the program which is running HWnd's window~1612
    -compare the file name returned against a list of file names
      associated with stored application states~1614
    -if find a match, set the new entry's AppState equal to the
      state associated with the matching file name~1618
    -else if the file name returned by MSW GetModuleFileName is
      that associated with a MSW file for running MS-DOS applications
      in a window~1620
      -call MSW GetWindowText for HWnd to get the text of its
        window's title bar~1622
      -compare the text returned with a list of text associated
        with application states~1624
      -if find a match, set the new entry's AppState equal to
        the state associated with the matching text~1628
    -if the new entry's AppState is still empty~1630
      -create a new temporary logical state for its
        application~1632
      -set the new entry's AppState equal to the new temporary
        logical state~1634
    -if a call to MSW GetWindow with GW_OWNER for HWnd's window
      indicates the window is a dialog box~1636
      -call MSW GetWindowText for the caption text of the dialog
        box~1638
      -if that text corresponds to the name of a sub-state
        within the AppState of the new entry~1640
        -change the new entry's AppState to that sub-
          state~1642
      -else~1644
        -create a temporary sub-state in the state stored in
          the current entry's AppState~1646
        -place that sub-state in the current entry's
          AppState~1648
    -return with the SelectedEntry~1650

```

FIG. 74

```
-LanguageContextTracking()~1714
  -call MSW GetFocus to get the handle of the window currently having
  the focus~1716
  -use MSW SendMessage to send the focus window the WM_GETDLGCODE
  message to find out if the focus window is a Multi-Line Edit control
  (MLE)~1718
  -if it is an MLE~1720
    -use MSW SendMessage to send EM_GETSEL to the MLE to get the
    character index of the starting position of the current
    selection~1722
    -use MSW SendMessage to send EM_LINEFROMCHAR to the MLE with
    the character index of the start of the current selection to
    get the line number in the MLE of the line on which the current
    selection starts~1724
    -use MSW SendMessage to send EM_GETLINE to the MLE with the
    line number of the current line to get a copy of that line~1726
    -use MSW SendMessage to send EM_LINEINDEX to the MLE with the
    line number of the current line to get the character index of
    start of that line~1728
    -subtract the index of the start of the current line from the
    index of the start of the current selection to determine the
    position in the copy of the current line of the start of the
    current selection~1730
    -starting backward from that position, look in the current line
    for last complete word before the current selection, and if
    that last complete word extends back into the previous line
    look for it in that previous line by using EM_LINEFROMCHAR AND
    EM_GETLINE~1732
    -if there is such a last complete word, set LanguageContext
    equal to it~1734
    -else, set LanguageContext to Null~1736
    -return~1738
  -else if CurrentAppState is associated with an external application
  which has a predefined interface for providing language context~1740
    -send a message to that predefined interface to obtain its
    language context~1742
    -set language context equal to that context~1744
    -return~1746
  -...
  -set LanguageContext to Null~1748
  -return~1750
```

FIG. 75

```

-CommandTracking()~1752
  -clear the CommandPhraseList~1754
  -if a call to MSW GetSystemDebugState returns SDS_MENU, indicating a
    menu is currently active~1756
    -for the menu handle of each entry in MenuStack~1758
      -call GetMenuCommandPhrases~1760
  -else~1762
    -call MSW GetActiveWindow to get the handle of the currently
      active window~1764
    -if a call to MSW GetMenu for the active window returns a menu
      handle, call GetMenuCommandPhrases for the menu~1766
    -if a call to MSW GetSystemMenu returns a menu handle to a copy
      of the system menu, call GetMenuCommandPhrases for the copy of
      the system menu~1768
    -use one or more calls to MSW GetWindow to perform a tree
      search for the handles of all windows, if any, included in
      active window~1770
    -for each window handle obtained~1772
      -if a call to MSW SendMessage sending the window a
        WM_GETDLGCODE message returns an indication the window is
        not a control window, skip to the iteration for the next
        window handle~1774
      -else if a call to IsWindowClickable indicates the window
        is not clickable, skip to the iteration for the next
        window handle~1776
      -else~1778
        -add an empty CommandPhraseEntry in the
          CommandPhraseList~1780
        -call MSW SendMessage to send the window a WM_GETTEXT
          message to get the control's associated text~1782
        -if the value returned in response to the
          WM_GETDLGCODE message indicated the window is a
          static control~1784
          -if the control's text has an accelerator, save
            a command to feed the accelerator key to the
            JournalPlaybackProc in the CommandPhraseEntry's
            CommandOutput~1788
          -else~1790
            -delete the empty CommandPhraseEntry
              created for this window handle~1792
            -skip to the iteration for the next window
              handle~1794
        -call StripControlOrMenuItemName with String equal
          the control's text and TextType equal Control~1796
        -if StripControlOrMenuItemName returns with an empty
          ReturnStringList, delete the current window's
          CommandPhraseEntry and skip to iteration for next
          window~1798
        -else~1800
          -place the ReturnStringList's first string in
            the CommandPhraseEntry's CommandPhrase field,
            enclosed in "[ ]"~1802

```

FIG. 76

```

        -if the CommandPhraseEntry's CommandOutput is
        empty fill it with a "ControlPick[first string]"
        script command~1804
        -if the ReturnStringList has a second
        string~1806
            -add a copy of the CommandPhraseEntry to
            the CommandPhraseList and copy the second
            string enclosed in "[]" into its
            CommandPhrase field~1808
            -if the additional CommandPhraseEntry's
            CommandOutput is empty fill it with a
            "ControlPick[second string]" script
            command~1810
    -check to see if there is a tracking state in the tracking state
    cache which includes the exact same collection of command phrases as
    the active window's CommandPhraseList~1812
    -if so~1814
        -make the matching tracking state the CurrentTrackingState~1816
        -set the matching tracking state's LastUsedTime to the current
        time~1818
    -else~1820
        -create a new, empty, tracking state~1822
        -for each CommandPhraseEntry of the CommandPhraseList~1824
            -call FindOrMakeMatchingWord for the CommandPhrase~1826
            -place the word ID, if any, returned by
            FindOrMakeMatchingWord in the new tracking state~1828
            -load the word ID's associated ExtraData field in the new
            tracking state with the value of the CommandPhraseEntry's
            CommandOutput~1830
            -if the tracking state cache has the maximum number of tracking
            states recorded in it, delete from the cache the tracking state
            with the oldest LastUsedTime~1832
            -store the new tracking state in the tracking state cache~1834
            -make the new tracking state the CurrentTrackingState~1836
            -set the new tracking state's LastUsedTime to the current
            time~1838
    -return~1840

```

FIG. 76 CONT.

```

-CommandPhraseList,~1842
    -a list of CommandPhraseEntry structs~1844, each containing
        -CommandPhrase~1846
        -CommandOutput~1848
        -MenuHandle~1850
        -MenuItemPosition~1852

```

FIG. 77

```

-GetMenuCommandPhrases(hmenu)~1860
  -set NumberOK and LastItemWasSeparatorOrNumber to false~1862
  -call MSW GetMenuItemCount to get number of items in the menu for
  which this subroutine was called~1864
  -for each of those items starting with the first~1866
    -call MSW GetMenuItemID to get the menu item's ID~1868
    -if MSW GetMenuItemID returns an indication the menu item is a
    separator, set LastItemWasSeparatorOrNumber to true~1870
    -else~1872
      -create an additional CommandPhraseEntry in the
      CommandPhraseList~1874
      -call MSW GetMenuString to get the menu item's
      spelling~1876
      -if LastItemWasSeparatorOrNumber is true, set NumberOK to
      true~1878
      -else set NumberOK to false~1880
      -call StripControlOrMenuItemName with String equal to the
      menu item's spelling, with TextType equal Menu, and with
      the current value of NumberOK~1882
      -if StripControlOrMenuItemName returns with an empty
      ReturnStringList, delete the CommandPhraseEntry~1884
      -else~1886
        -place the first string in the ReturnStringList in
        the CommandPhraseEntry's CommandPhrase enclosed in
        "["~1888
        -place a "MenuPick[first string]" script command in
        the CommandPhraseEntry's CommandOutput~1890
        -place the menu's menu handle in the
        CommandPhraseEntry's MenuHandle and the menu item's
        position in the CommandPhraseEntry's
        MenuItemPosition~1892
        -if there is a second string in the
        ReturnStringList~1894
          -add a copy of the CommandPhraseEntry to the
          CommandPhraseList~1896
          -place the second string into the copy's
          CommandPhrase field enclosed in "["~1898
          -place a "MenuPick[second string]" script
          command in the copy's CommandOutput~1900
        -return~1902

```

FIG. 78


```

-MenuPick(String)~1954
  -clear the KeystrokeHistoryString~1958
  -if a call to MSW GetSystemDebugState returns SDS_MENU, indicating
  that a menu is currently active~1960
    -for each MenuEntry in MenuStack, starting at the end~1962
      -clear CommandPhraseList~1964
      -call GetMenuCommandPhrases for the MenuEntry's
      MenuHandle~1966
      -for each CommandPhraseEntry placed in the
      CommandPhraseList by GetMenuCommandPhrases~1968
        -if the spelling within the "[]" of its CommandPhrase
        matches String~1970
          -add to the KeystrokeHistoryString the arrow
          keystrokes necessary to move from the position
          of the MenuEntry's MenuItemID to that associated
          with the CommandPhraseEntry's
          MenuItemPosition~1972
          -add "enter" to the KeystrokeHistoryString~1974
          -use the JournalPlaybackProc to playback the
          KeystrokeHistoryString~1976
          -return~1978
        -add an "escape" key to the KeystrokeHistoryString~1980
        -delete the last MenuEntry from the end of the
        MenuStack~1982
  -else~1984
    -call MSW GetActiveWindow, GetMenu, and GetSystemMenu to get
    the active window's main menu and its system menu~1986
    -clear the CommandPhraseList~1988
    -for the active window's menu call GetMenuCommandPhrases~2000
    -for the active window's system menu call
    GetMenuCommandPhrases~2002
    -for each CommandPhraseEntry in the CommandPhraseList~2004
      -if the spelling within "[]" of its CommandPhrase matches
      String~2006
        -if the CommandPhraseEntry's MenuHandle is that of
        active window's main menu, add to the
        KeystrokeHistoryString an "Alt" followed by the arrow
        keystrokes necessary to go from first item in the
        menu to the CommandPhraseEntry's MenuItemPosition,
        followed by an "Enter"~2008
        -else if its menu handle is that of the active
        window's system menu, add to the
        KeystrokeHistoryString an "Alt-Spacebar" followed by
        the arrow keystrokes necessary to go from the first
        item in the system menu to the item represented by
        the MenuItemID of the matching CommandPhraseEntry,
        followed by an "Enter"~2010
        -use the JournalPlaybackProc to play keystrokes back
        to active application~2012
        -return~2014
    -display an error message~2016
    -return~2018

```

FIG. 81

```

-ControlPick(String)-1956
  -call MSW GetActiveWindow to get the handle of the currently active
  window-2020
  -use one or more calls to MSW GetWindow to perform a tree search for
  the handles of all child windows, if any, included in the active
  window-2022
  -for each child window handle obtained-2024
    -if using MSW SendMessage to send the child window the
    WM_GETDLGCODE message returns an indication the child window is
    not a non-static control, skip to the iteration for the next
    child window-2026
    -call MSW SendMessage to send the child window a WM_GETTEXT
    message to get the control window's associated text-2028
    -call StripControlOrMenuItemName with window's text as String
    and with TextType equal to Control-2030
    -if any string in the ReturnStringList returned by
    StripControlOrMenuItemName matches the String with which
    ControlPick was called-2032
      -if a call to IsWindowClickable for the window returns a
      clickable point, uses the JournalPlaybackProc to send the
      window the WM_LBUTTONDOWN and then the WM_LBUTTONUP
      messages at that point-2034
      -return-2036
    -if no control window with text matching ControlPick's String is
    found, display an error message.-2038
  -return-2040

```

FIG. 82

```

-PropertiesTabOfAdvancedModifyWordDialog(Word, State)-2054
  -...
  -message loop-2056
    -call MSW GetMessage-2058
    -if message is-2060
      -...
      -OK-2062
      -if Forget Training button is pressed, remove word's
      helper model from .USR file-2064
      -...
    -...
  -...

```

FIG. 85

APPROVED	O.G. FIG.	
BY	CLASS	SUBCLASS
WETSMAN		




Figure 84




Figure 86

2692910" EFB28880

APPROVED	O.G. FIG.	
BY	CLASS	SUBCLASS
FTSMAN		




Figure 89